



GRANULAR ACTIVATED CARBON CR46B

CR46B is a granular activated carbon produced from bituminous coal through high temperature steam activation under stringent quality control. It has a large surface area, high mechanical hardness and high pore volume.

FEATURES AND BENEFITS

- ◆ High adsorption capacity and efficiency
 - ◆ Hard and durable
 - ◆ Highly developed pore structure

SPECIFICATIONS

US Standard Sieve	
Mesh Size:	4X6
Greater than 4	10% maximum
Less than 6	5% maximum
MPD (mm)	3.6 minimum
Carbon Tetrachloride Number (%)	60 minimum
Iodine Number (mg/g)	1050 minimum
Hardness Number	95 minimum
Moisture (as packed)	5% maximum
Bulk Density (g/cc)	0.48 typical

Packaged in 55-lb. poly bags, 200-lb. fiber drums, or 1100-lb. super sacks.
All of the above test methods are performed by ASTM protocol for granular activated carbon.

This information has been gathered from standard reference materials and/or test data that is assumed to be accurate and reliable. Carbon Resources, LLC. only warrants that this product will meet the above described published specifications and makes no other warranties of any kind either expressed or implied including but not limited to fitness for a particular purpose or application. Buyer assumes all liability and risk that may arise from the use of this product.