



PELLETIZED ACTIVATED CARBON CR4B-AW

CR4B-AW is an acid-washed, 4.0mm, extruded (pellet) activated carbon produced from bituminous coal by a high temperature activation process under stringent quality control. It has a large surface area, high mechanical hardness, high pore volume and chemical stability.

FEATURES AND BENEFITS

- ◆ High adsorption capacity and efficiency
 - ◆ Hard and durable
 - ◆ Highly developed pore structure

SPECIFICATIONS

Particle Shape	4.0 mm diameter nominal
Carbon Tetrachloride Activity (%)	60 minimum
Iodine Number (mg/g)	1050 minimum
Hardness Number	95 minimum
Moisture % (as packed)	5 maximum
Apparent Density (g/cc)	0.47 typical
Acid Soluble Ash (%)	Less than 1
pH	4-7

Packaged in 55-lb. bags, 200-lb. drums or 1100-lb. super sacks.

All of the above test methods are performed using ASTM protocol for activated carbon

This information has been gathered from standard reference materials and/or test data that is assumed to be accurate and reliable. Carbon Resources, LLC. only warrants that this product will meet the above described published specifications and makes no other warranties of any kind either expressed or implied including but not limited to fitness for a particular purpose or application. Buyer assumes all liability and risk that may arise from the use of this product.