



GRANULAR ACTIVATED CARBON CR610A

CR610A is a granular activated carbon produced from select coal by a high temperature steam activation process under stringent quality control. It has a large surface area, high mechanical hardness, unique pore size distribution, low density and chemical stability.

FEATURES AND BENEFITS

- ◆ High adsorption capacity and efficiency
 - ◆ Hard and durable
 - ◆ Highly developed pore structure

SPECIFICATIONS

US Standard Sieve	
Mesh Size:	6x10
Greater than 6	6% maximum
Less than 10	5% maximum
Iodine Number (mg/g)	1000 minimum
Molasses Number	300 typical
Hardness Number	90 typical
Moisture (as packed)	3% maximum
Apparent Density (g/cc)	0.32 - 0.34 typical
Bulk Density (lb./cf)	20-22
Water Soluble Ash	0.25% typical
pH	8-8.5 typical

Packaged in 44-pound bags or 825-pound supersacks.
All of the above test methods are performed using ASTM protocol for granular activated carbon

This information has been gathered from standard reference materials and/or test data that is assumed to be accurate and reliable. Carbon Resources, LLC, only warrants that this product will meet the above described published specifications and makes no other warranties of any kind either expressed or implied including but not limited to fitness for a particular purpose or application. Buyer assumes all liability and risk that may arise from the use of this product.